




REV	2	1	
	CONTENT	CHK	DATE
V0.0	CONTENT	MYZ	21.07.06



Electrical :

1. Rated Voltage : UL 300V IEC 320V
 2. Rated Current : 15A 20A
 3. Withstanding Voltage : AC1600V/1Min.
 4. Operating Temperature : -40°C~+105°C
 5. RoHS Compliance
 6. Safty Approval : 
 7. "★" is the key quality control point.

PCB Layout



SECTION A-A



2EGTRC - 5.0 -XXP - X X - 100

① ② ③ ④ ⑤ ⑥

- ① Series NO. ④ 1 Single Pitch
2 Double Pitch
- ② Pitch ⑤ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White
- ③ Poles
02 02Contacts
03 03Contacts
... 24 24Contacts
- ⑥ Customer Request: 100--Standard

2	PIN	XX	P	BRASS	Tin Plated
1	HOUSING	XX	1	PA66 UL94V-0	SEE NOTE
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	MYZ	DATE	21.07.06	SIZE	A4 UNITS mm SHEET/OF 1/1
CHK.	DATE		SCALE	1:1	
APP.	DATE				
 宁波冠泰电子有限公司 NINGBO GOLTEN ELECTRONICS CO., LTD.			NAME	2EGTRC-5.0-XXP-XX-100	
			DWGNO.	XXXX	

Total Pitch Tolerances in mm									Nominal dimension range in mm									$\perp$		$\equiv$	--- //		
over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 0	over 10		over 0	over 100	over 150
to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10		all	to 100	to 150	
± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.44	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5