



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 10/10/14'		

- Notes:
- Material:
    - Housing: High Temperature LCP, UL94V-0 Roted Color: Black.
    - Contacts: Copper Alloy.
    - Stator: Copper Alloy.
    - Shell: Stainless Steel.
  - Specifications:
    - Operate Temperature:  $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
    - Insulation Resistance: 1000M $\Omega$  Min.
    - Contact Resistance: 30m $\Omega$  max.
    - Withstanding Voltage: 500V AC 1min.
    - Operating Voltage: 30V AC/DC.
    - Current Rating: 1.0A
  - Product Number Code:

DS1139-04 - XX X X X X X X

- Packing Type  
R: Tape On Reel
- Shell Plating  
S: Stainless
- Housing color  
B: Black
- Contact Plating  
4: Selective 3u" gold
- Mounting type  
S: SMT type
- Connector type  
S: Socket
- No. of contacts  
08:08pin

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	
X.	±0.60	X.	±5°	UNITS	mm	Micro SD Card H=1.5mm SMT Type	
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1139-04 SERIES
.XX	±0.25	.XX	±2°	<b>晨翔电子有限公司</b> <b>CONNFLY® CONNFLY ELECTRONIC CO., LTD</b>			
DRAWING TYPE		CUSTOMER					
SCALE	1:1	SHEET	1 OF 1				
DRAWING NO.		C-DS1139-04-XXXXXX-A					